

Insulation Coating (Glass · Silk) Dimension

●SG,DG,SS,DS

【Unit: mm】

Base Wire	SG		DG		SS		DS	
	Minimum	Maximum	Minimum	Maximum	Minimum	Maximum	Minimum	Maximum
0.06			0.06	0.230				
0.07			〃	0.240				
0.08			〃	0.250				
0.09			〃	0.260				
0.10			〃	0.270				
0.12			〃	0.300				
0.14	0.06	0.288	0.10	0.388				
0.15	〃	0.298	〃	0.398				
0.16	〃	0.308	〃	0.408	0.015	0.213	0.030	0.246
0.18	〃	0.328	〃	0.428	〃	0.223	〃	0.267
0.20	〃	0.348	〃	0.448	0.020	0.258	0.035	0.298
0.23	〃	0.378	〃	0.478	〃	0.290	〃	0.323
0.26	〃	0.410	〃	0.510	〃	0.320	〃	0.353
0.29	〃	0.440	〃	0.540	〃	0.350	〃	0.385
0.32	〃	0.470	〃	0.570	〃	0.380	〃	0.415
0.35	〃	0.500	〃	0.600	〃	0.415	〃	0.453
0.40	〃	0.550	〃	0.650	〃	0.465	0.040	0.510
0.45	〃	0.600	〃	0.700	〃	0.520	〃	0.560
0.50	〃	0.650	〃	0.750	〃	0.570	〃	0.610
0.55	〃	0.710	〃	0.830	〃	0.620	〃	0.660
0.60	〃	0.760	〃	0.880	〃	0.670	〃	0.710
0.65	〃	0.810	〃	0.920	0.025	0.710	〃	0.780
0.70	〃	0.860	〃	0.980	〃	0.760	〃	0.840
0.75	〃	0.910	〃	1.030	〃	0.840	〃	0.870
0.80	〃	0.960	〃	1.080	〃	0.860	〃	0.940
0.85	〃	1.010	〃	1.130	〃	0.940	〃	0.970
0.90	〃	1.060	〃	1.180	〃	0.960	〃	1.040
1.00	〃	1.170	〃	1.290	0.03	1.080	0.050	1.160

Name	Code	Max Temp [°C]
Single Silk	SS	105
Double Silk	DS	105
Single Glass	SG	180
Double Glass	DG	180